

DESIGN & APPLICATION GUIDE

Digital Liquids Leak Detection Systems For Indoor Applications



INTRODUCTION

TTK Leak Detection and Locating Systems For Indoor Design and Application Guide is mainly addressed to engineering consultants, contractors and end users. This guide, illustrated with a great quantity of drawings and diagrams, showing the TTK leak detection and locating systems as FG-NET, FG-BBOX, FG-ALS4's typical layouts and applications in building environment.

INDEX

NTRODUCTION	2
PRODUCTS LIST	3
PART I DESIGN LAYOUTS	5
1.1 General Description	ō
1.2 Alarm Units	6
1.2.1 Digital Unit: FG-NET	5
1.2.2 Digital Unit: FG-SYS	7
1.2.3 Satellite Device: FG-BB0X	3
1.2.4 Eight Zone Alarm & Locating Unit: FG-ALS8	7
1.2.5 Eight Zone Alarm & Locating Unit For Hydrocarbon: FG-ALS8-0D	7
1.2.6 Four Zone Alarm & Locating Unit: FG-ALS410	נ
1.2.7 Four Zone Alarm & Locating Unit For Hydrocarbon: FG-ALS4-0D	נ
1.2.8 Alarm Unit: FG-A	1
1.2.9 Alarm Unit: FG-A-0D	1
1.2.10 Alarm Unit: FG-STAD	2
1.3 Point Sensors	3
1.3.1 Addressable Water Point Sensor: FG-ECP	3
1.3.2 Addressable Hydrocarbon Point Sensor: FG-ODP	4
1.4 Boxes	C
1.4.1 Diversion Box: FG-DTC	5
1.4.2 Addressable Box: FG-DTCS.	5
1.4.3 Mixed Layout With FG-DTC & FG-DTCS Boxes	5
1.4.4 'Cut-To-Length' Addressable Box: FG-DCTL / FG-DCTL-R	5
1.4.5 Interface Box: FG-DOD	1
1.4.6 Point Sensor Diversion Box: FG-DOP	3
1.4.7 Mixed Layout With FG-DOD & FG-DOP Boxes	3
1.5 Horizontal Layout On Three Outputs	1
1.6 Vertical Layout On Three Outputs	1
1.0 Externel Delaye Dev 50 DELAYC	J 1
1.8 External Relays Box: FG-RELATS	I
PART 2 APPLICATIONS	2
2.1 Data Center, Air-Conditioner Room Applications	2
2.2 Iechnical Equipments	2
2.3 Indoor Water Pipe Application	3
2.4 Application for Several Levels in One Building	4

This Design Guide with its photos, illustrations and charts was carefully prepared, but it is only intended for promotional use. TTK cannot guarantee that the information given contains no errors or omissions and will accept no responsibility related to the usage of its equipment. TTK's only obligations are those set forth in the Standard Terms and Conditions of Sale and will not under any circumstances be held liable for any incidental, indirect or consequential damages arising from the sale, resale or misuse of this product. The purchasers are the sole judges of the product's adaptability to the use for which it is destined. FG-NET, FG-SYS and TOPSurveillance are trademarks of TTK S.A.S. © TTK 2019

TTK Headquarters / 19, rue du Général Foy / 75008 Paris / France / T : +33.1.56.76.90.10 / F : +33.1.55.90.62.15 / www.ttk.fr / ventesfdttk.fr

TTK UK Ltd. / 3 Luke Street / London EC2A 4PX / United Kingdom / T: +44 207 729 6002 / F: +44 207 729 6003 / www.ttkuk.com / sales@ttkuk.com

TTK Pte Ltd. / #09-05, Shenton House, 3 Shenton Way / Singapore 068805 / T: +65.6220.2068 / M: +65.9271.6191 / F: +65-6220.2026 / www.ttk.sg / sales@ttk.sg

TTK Asia Ltd. / 2107-2108 Kai Tak Commercial Building / 317 Des Voeux Road Central / Hongkong / T: +852.2858.7128 / F: +852.2858.8428 / www.ttkasia.com / info@ttkasia.com

- TTK Middle East FZC0 / Building 6EA, Office 510 PO Box 54925 / Dubai Airport Free Zone / UAE / T: +971 4 70 17 553 / M: +971 50 259 66 29 / www.ttkuk.com / cgalmiche@ttk.fr
- TTK Deutschland GmbH / Berner Strasse 34 / 60437 Frankfurt / Deutschland / T : +49(0)69-95005630 / F : +49(0)69-95005640 / www.ttk-gmbh.de / vertrieb@ttk-gmbh.de

TTK North America Inc / 1730 St Laurent Boulevard Suite 800 / Ottawa, ON, K1G 5L1 / Canada / T : +1 613 566 5968 / www.ttkcanada.com / info@ttkcanada.com
 Thomas Sales & Marketing Inc. TTK Master Distributor For USA /7200 W 66th St/Bedford Park, IL 60638/The United States/T: +1 630-518-4724 / www.ttkusa.com / dmolk@ttkusa.com

PRODUCTS LIST

Belowing table lists all products you will find in this guide. For each item, a real product photo, its 3D view in drawings as well as a brief introduction are presented to ease your reading.

Product Photo	& 3D View	Reference	Description			
Alarm Units						
	TIK	FG-NET	Digital touch-screen leak detection panel, it serves as a control alarm panel, it activates audible alarm, display location of the initial point of the leak, active the relays associated. Compatible with water, bases, acid and hydrocarbon leak detection digital sense cables.			
Tik	1114	FG-NET-LL	The principal difference with FG-NET panel is, FG-NET-LL is designed to be used with hydrocarbon FG-OD range of sense cables / point sensors exclu- sively, for industry Long Line 'LL' applications. For more details, ref to «TTK Fuel Leak Detection Airport / Pipeline / Storage Tank Design Guide».			
	AV	FG-ALS8 / FG-ALS4	Eight / Four zones alarm & locating unit, these 2 panels are designed to be used with analog sense cables / point sensors for water and acids leak detection.			
TIK		FG-ALS8-OD / FG-ALS4-OD	The principal difference with FG-ALS8/FG-ALS4 is, FG-ALS8-OD/FG-ALS4- OD alarm unit is designed to be connected with hydrocarbon FG-OD range of sense cables / point sensors exclusively.			
		FG-SYS	Digital leak detection panel, it serves as a control alarm panel, it activates audible alarm, display location of the initial point of the leak, active the relays associated. Compatible with water, bases and acid leak detection sense cables / point sensors only.			
in the second se	• • • • • •	FG-A / FG-A-OD	Analog leak detection panel without location, FG-A is designed to be used with analog sense cables / point sensors for water and acids leak detection; FG- A-OD is designed to be connected with hydrocarbon FG-OD range of sense cables / point sensors exclusively.			
And the formation of the second secon		FG-STAD	The FG-STAD allows TTK hydrocarbon FG-OD range of sense cables and point sensors to function in a fully stand-alone mode, without fixed voltage power supply, thanks to its embedded battery.			
Satellite Devices						
11k	nu	FG-BB0X	FG-NET's satellite device - 2 circuits 'black box'. It expands FG-NET to ma- nage two additional circuits of sense cables with up to 1200 metres of addi- tional sense cables.			
fik	ANK	FG-BBOX-LL	The principal difference with FG-BBOX is, FG-BBOX-LL is designed to be connected with hydrocarbon FG-OD range of digital sense cables / point sen- sors exclusively, for industry Long Line 'LL' applications. For more details, ref to «TTK Fuel Leak Detection Airport / Pipeline / Storage Tank Design Guide».			
fik	artic	FG-RELAYS	FG-NET's satellite device - 'External relays box'. It adds a set of 24 configu- rable external relays to the FG-NET, thus allows FG-NET to drive external devices.			
Sense Cables		1				
	- THE MERIDIAN	FG-EC	Preterminated digital water and bases sense cable with location; it exists in 3, 7 and 15 metres. The cable is made with special Low Smoke Zero Halogen materials.			
S	ATTACHTER TO THE STATE OF STAT	FG-ECB	Preterminated digital water and bases sense cable with location, equipped with an external polyethylene based braided jacket and is specially designed for pipes solution; it exists in 3, 7 and 15 metres.			
	AND MANDER MANDER	FG-AC	Preterminated digital acid sense cable with location; it exists in 3, 7 and 15 metres.			

PRODUCTS LIST (FOLLOWING)

Product Photo	& 3D View	Reference	Description			
Sense Cables (following)						
		FG-0D	Preterminated digital hydrocarbon/oil sense cable, with location; it exists in 3, 7, 12 and 20 metres. For oil sense cable applications, ref to «TTK Fuel Leak Detection Airport / Pipeline / Storage Tank Design Guide».			
Q	ALTER THE REAL PROPERTY OF THE	FG-ECS	Preterminated digital water sense cable, with location; it exists in 3, 7, 15 metres and in 400 metre random. The cable is made with special Low Smoke Zero Halogen materials.			
Point Sensors						
		FG-ECP	Point sensor for water and base leak detection. Available in two models: sense cable in ''U'' form and ''L'' form to suit different environments.			
0		FG-0DP	Point sensor for liquid hydrocarbon and non-conductive solvent leak detec- tion.			
Boxes						
		FG-DTC	Diversion box for 'TTK BUS 8723', allows breaking up a detection circuit into two parts.			
a		FG-DTCS	Addressable box for one water or acids cable, on 'TTK BUS 8723' (sector mode), allows creating an address on the panel for the sense cable connected.			
.		FG-DCTL / FG-DCTL-R	Addressable box allows the connection of one analog sense cable (1 to 45m, "Cut-To-Length") to the main BUS wire from the digital panel. 2 references are available: FG-DCTL and FG-DCTL-R. The only difference: FG-DCTL-R is equipped with a relay (230Vac-1A), activated in case of leak; not for FG-DCTL.			
· · · · ·		FG-DOD	OD BUS interface box, for Integration of FG-OD cables on a water & acids 'TTK BUS 8723'.			
		FG-DOP	Point sensor diversion box. It is a connection box for integration of point sen- sor FG-0DP on an 0D BUS 8771.			
Accessories						
0		FG-CLC	Leader cable on TTK BUS 8723, for connecting FG-NET/FG-SYS/FG-BBOX digital unit and first sense cable or between two water / acids digital sense cables in a non-risk area.			
		FG-CLOD	The difference with FG-CLC is, FG-CLOD is a leader cable on 'OD BUS 8771', for connecting FG-NET-LL or FG-BBOX-LL digital unit and first hydrocarbon sense cable or between two hydrocarbon sense cables in a non-risk area.			
	VIII THE REAL PROPERTY OF	CF-EC100 CF-OD50	Hold down clips with cold glue to fix sense cable lengths. Recommended at corner and every 1.5 metres.			
	- The a	ES-EC (green) ES-OD (orange)	Tags, for caution use, recommended every 3 metres or where needed.			
Streening .		FG-TMC (black) FG-TMOD (orange)	Modular end termination plug is used to terminate each circuit of sense cables.			

PART I DESIGN LAYOUTS

each zone or all in one zone)

This part offers layout examples of locating and non-locating systems in building environment, classified by alarm unit.

1.1 General Description Below are some technical limits of the capacity of principal control panels: FG-BBOX or FG-BBOX-LL FG-NET or FG-NET-LL **Digital Unit** Digital Unit 2 CIRCUITS 3 CIRCUITS For FG-NET, up to 40 sense cables can be connected on each circuit. For FG-BBOX, up to 40 sense cables can be connected on each circuit. For FG-NET-LL, up to 59 sense cables can be connected on each circuit. For FG-BBOX-LL, up to 59 sense cables can be connected on each circuit. FG-ALS8 or FG-ALS8-OD FG-SYS Digital Unit Alarm Unit 8 ZONES **3 CIRCUITS** For FG-ALS8, up to 100 metres of sense cables can be connected on each circuit. For FG-SYS, up to 40 sense cables can be connected on each circuit. For FG-ALS8-OD, up to **8** lengths of sense cables can be connected on the unit, no matter how the 8 cables are connected (on each zone or all in one zone) FG-ALS4 or FG-ALS4-0D FG-A or FG-A-Alarm Unit OD or FG-STAD Alarm Unit 4 ZONES 1 ZONE For FG-ALS4, up to 45 metres of sense cables can be connected For FG-A, up to 15 metres of sense cables can be connected. on each circuit. For FG-A-OD, up to **20** metres of sense cables can be connected. For FG-ALS4-0D, up to 4 lengths of sense cables can be connec-• For FG-STAD, up to 20 metres of sense cables can be connected. ted on the unit, no matter how the 4 cables are connected (on

	Control Panels	Numbers of Integrated Circuits	Maximum Capacity Per Circuit
Water & Acids Leak Detection Panels	FG-NET	3	40 cables
	FG-SYS	3	40 cables
	FG-BBOX	2	40 cables
	FG-ALS8	8	100 metres
	FG-ALS4	4	45 metres
	FG-A	1	15 metres
Hydrocarbon Leak Detection Panels	FG-NET-LL	3	59 cables
	FG-BBOX-LL	2	59 cables
	FG-ALS8-OD	8	8 cables (with no sense cables in 7 other circuits)
	FG-ALS4-0D	4	4 cables (with no sense cables in 3 other circuits)
	FG-A-OD	1	1 cable
	FG-STAD	1	1 cable

Figures 1.1 Capacity of principal control panels

1.2.1 Digital Unit: FG-NET

FG-NET locating system includes basically: (figure 1.2.1)

- FG-NET digital unit.
- TTK BUS 8723 jumper cable (for connecting between panel and the first sense cables in this layout).
- Digital sense cable (FG-EC in this layout, standard lengths are 3, 7 and 15 metres).
- End termination (used at end of last sense cables, mark the termination of one circuit).
- Accessories:
 - Hold-down clips (fix sense cable, stick on the floor);
 - Tags (caution use).



In below example of 3 circuits layout with FG-NET, there are:

- FG-NET digital unit.
- TTK BUS 8723 jumper cable:
 - for connecting panel and the first water / acids sense cables for circuits 2&3;
 - for connecting panel and interface box FG-DOD (explanation see 4 lines below) in circuit 1 in this layout.
- Digital sense cables:
 - Water sense cables FG-EC; acids sense cables FG-AC (standard lengths are 3, 7 and 15 metres) in circuit 2 & 3;
 - Hydrocarbon sense cables FG-OD (standard lengths are 3, 7, 12 and 20 metres) in circuit 1.
- Interface box FG-DOD in circuit 1: it splits TTK BUS 8723 into 2 outputs including OD BUS 8771 for FG-OD sense cable connection.
- End termination and accessories same as figure 1.2.1.



FG-NET-LL digital unit uses the same principal. It has OD BUS 8771 output. It is designed to be connected to hydrocarbon FG-OD range of sense cables / point sensors exclusively, for industry Long Line 'LL' applications. For more details, ref to «TTK Fuel Leak Detection Airport / Pipeline / Storage Tank Design Guide».

1.2.2 Digital Unit: FG-SYS

Concerning to design layout, FG-SYS digital unit is very similar to FG-NET digital unit, they have the same technical limit on cable lengths. The difference is FG-SYS is designed for water and acids leak detection, thus not compatible with hydrocarbon sense cables / hydrocarbon point sensors.

Water and acids sense cables can be mixed in the same circuit.



Figure 1.2.2 Basic layout of FG-SYS with 3 circuits

1.2.2.1 Layout Comparison Between TTK & Other System



For TTK Digital System (FG-NET, FG-SYS):

- 1 sole digital panel can monitor all 3 areas, no need of any slave module.
- It detects multileaks: 4 leaks (even simultaneous) on 3 areas.
- It detects multileaks + cable break fault: 4 leaks and 1 cable break.



For Other Traditional System:

- 1 master panel + 3 slave modules are enquired to monitor all 3 areas.
- In case of multileak: only the first leak can be located precisely; others are detected but without precise location.
- In case of multileaks + cable break fault: no leak can be detected after the cable break faults in the same area.

1.2.3 Satellite Device: FG-BBOX

- The FG-BBOX is a satellite device (or a "daughter panel") of the TTK FG-NET digital unit. It expands FG-NET to manage two additional circuits of sense cables with up to **1200 metres (or 80 lengths)** of additional sense cables.
- FG-BBOX facilitates installation by eliminating the need to draw jumper cables between the monitoring panel and sensing cables through the building to a given area or floor thanks to its Ethernet connectivity.



Figures 1.2.3.1 FG-BBOX connection with FG-NET on Ethernet network

FG-BB0X-LL digital unit uses the same principal. It has OD BUS 8771 output. It is designed to be connected to hydrocarbon FG-OD range of sense cables / point sensors exclusively, for industry Long Line 'LL' applications. For more details, ref to «TTK Fuel Leak Detection Airport / Pipeline / Storage Tank Design Guide».

1.2.4 Eight Zone Alarm & Locating Unit: FG-ALS8

The FG-ALS8, eight zones alarm & locating system unit is designed to be used with analog sense cables: FG-ECS, FG-ACS or FG-ECX, FG-ACX, for water, base or acid leak detection.

- In the event of liquid leak or fault on the sense cables in any zone, the FG-ALS8 will respond as follows:
- An audible alarm is triggered and a relay is activated.
- The touch screen of the panel displays the zone, the location of the leak (to the **nearest metre**) and details of the fault (the type of fault leak or cable break).
- Report to the BMS via MODBUS /JBUS protocol.



Layout Explanation (Figure 1.2.4) :

- **8** detection zones are available.
- FG-ALS8 can control **up to 100m** of sense cable **per zone**.
- In total, up to 800m of sense cable per unit.
- In case of one zone has less than 100m, the unused length can not be transferred to another zone.

Figure 1.2.4 : Layout of FG-ALS8 with 8 zones

1.2.5 Eight Zone Alarm & Locating Unit For Hydrocarbon: FG-ALS8-OD

The FG-ALS8-OD, eight zones alarm & locating system unit for hydrocarbon leak detection is designed to be used exclusively with FG-OD hydrocarbon range of detectors.

In the event of liquid leak or default on the sense cables for each zone, the responses from the FG-ALS8-OD alarm & locating unit:

- An audible alarm is triggered and a relay is activated.
- The touch screen of the panel displays the zone, the location of the leak (on the cable) and details of the fault (the type of fault leak or cable break).
- Report to the DCS/SCADA/Safeguarding system via a JBUS/MODBUS protocol.



Figure 1.2.5 : Layout of FG-ALS8-OD with 8 zones

Layout Explanation (Figure 1.2.5):

- 8 detection zones are available.
- FG-ALS8-OD can control up to 1 address or 1 length (of 3, 7,12 or 20m) of sense cable or point sensor per zone.
- In total, up to 8 lengths (or 160m) of sense cables or point sensors per unit.
- Different possibilities of configurations are:
 - 1 cable per zone; or
 - 8 cables on the first output and leave all other seven outputs vacant, or
 - other possible connection.

Point detector can be connected in the place of sense cables, see 1.3.2.

For a system with FG-ALS8 or FG-ALS8-OD unit:

- Between 2 lengths of sense cables: up to 150m of jumper cables.
- Total length of jumper cables on a unit: up to **300m**.

1.2.6 Four Zone Alarm & Locating Unit: FG-ALS4

The FG-ALS4, four zones alarm & locating system unit is designed to be used with analog sense cables: FG-ECS, FG-ACS or FG-ECX, FG-ACX, for water, base or acid leak detection.

- In the event of liquid leak or fault on the sense cables in any zone, the FG-ALS4 will respond as follows:
 - An audible alarm is triggered and a relay is activated.
 - The touch screen of the panel displays the zone, the location of the leak (to the nearest metre) and details of the fault (the type of fault leak or cable break)
 - Report to the BMS via MODBUS /JBUS protocol.



Figure 1.2.6 : Layout of FG-ALS4 with 4 zones

1.2.7 Four Zone Alarm & Locating Unit For Hydrocarbon: FG-ALS4-OD

The FG-ALS4-OD, four zones alarm & locating system unit for hydrocarbon leak detection is designed to be used exclusively with FG-OD hydrocarbon range of detectors.

In the event of liquid leak or default on the sense cables for each zone, the responses from the FG-ALS4-OD alarm & locating unit:

- An audible alarm is triggered and a relay is activated.
- The touch screen of the panel displays the zone, the location of the leak (on the cable) and details of the fault (the type of fault leak or cable break).
- Report to the DCS/SCADA/Safeguarding system via a JBUS/MODBUS protocol.



Figure 1.2.7 : Layout of FG-ALS4-OD with 4 zones

For a system with FG-ALS4 or FG-ALS4-OD unit:

- Between 2 lengths of sense cables: up to 150m of jumper cables.
- Total length of jumper cables on a unit: up to 300m.

4 detection zones are available.

- FG-ALS4-OD can control up to 1 address or 1 length (of 3, 7, 12 or 20m) of oil sense cable or point sensor per zone.
- In total, up to 4 lengths (or 80m) of • sense cables or point sensors **per** unit.
- Different possibilities of configurations are:
 - 1 cable per zone; or
 - 2 cables in one zone et 0 cable in another · or
 - all of the 4 cables in one zone.

Point detector can be connected in the place of sense cables, see 1.3.2.

1.2.8 Alarm Unit: FG-A

The FG-A alarm unit is a non-locating unit. It is designed to be used with analog sense cables as FG-ECS, FG-ECX, FG-ACS and FG-ACX for water and acids leak detection.

Responses on the FG-A alarm unit:

- In the case of a leak, an audible alarm is triggered. The red LED on the front panel is switched on and the leak relay is activated.
- In the case of cable break, an audible alarm is triggered, the yellow LED on the front panel is switched on and the cable break relay is activated.



Figure 1.2.8 Layout with FG-A

1.2.9 Alarm Unit: FG-A-OD

The FG-A-OD alarm unit is a single sensor alarm unit. It is designed to be used exclusively with FG-OD hydrocarbon range of detectors for oil leak detection.

Responses on the FG-A-OD alarm unit:

- In the case of a leak, an audible alarm is triggered. The red LED on the front panel is switched on and the leak relay is activated.
- In the case of cable break, an audible alarm is triggered, the yellow LED on the front panel is switched on and the cable break relay is activated.



Figure 1.2.9 Layout with FG-A-OD

1.2.10 Alarm Unit: FG-STAD

The standalone alarm unit FG-STAD is designed to be used with the TTK FG-OD range of hydrocarbon leak detection sense cables, or the hydrocarbon point sensor, FG-ODP.

It monitors - in a fully stand-alone mode - one hydrocarbon leak point sensor or one sense cable.

No voltage supply is needed, the panel is supplied with an embedded battery.

There is no display on the FG-STAD panel. It is the interface between detectors and third-party supervision equipment thanks to its two singlepole outputs. One output reacts when the connected sense cable or point sensor is detected an oil leak, the other when a system fault appears.

FG-STAD Standalone Alarm Unit Up to 150 m of jumper cable TTK OD BUS 8771 between the pannel and the sense cable To a third-party supervision equipment

Figure 1.2.10 Layout with FG-STAD

Layout Explanation (Figure 1.2.10):

- The FG-STAD unit has 1 circuit.
- Up to 15 metres of sense cables (one length of FG-OD or a FG-ODP point sensor) can be connected on the FG-STAD.

1.3 Point Sensors

In some situations, point sensors (probes) may better adapt the specific environment than sense cables. Below are 2 Point Sensors, designed to be used with TTK digital units and alarm & locating system units for instant detection of liquid leaks.

1.3.1 Addressable Water Point Sensor: FG-ECP

- The FG-ECP, point sensor for water leak detection, is suitable to be used in environment such as lift pit and drip tray.
- The point sensor is available in two models: sense cable in "U" form and "L" form to suit different environments.
- It is designed to be used with FG-NET, FG-BBOX and FG-SYS digital units.
- Up to 40 x FG-ECP point sensors per digital unit circuit can be connected.
- FG-ECP point sensor can be mixed connected with FG-EC sense cables in one circuit on a digital unit (see figure 1.3.1.2).



Figure 1.3.1: Layout of FG-ECP with FG-NET



Figure 1.3.1.2: Layout of mixed connection of point sensors FG-ECP and digital sense cables FG-EC on a circuit of FG-NET digital unit

1.3.2 Addressable Hydrocarbon Point Sensor: FG-ODP

- The FG-ODP, point sensor for liquid hydrocarbon and non-conductive solvent leak detection, is suitable to detect hydrocarbon floating on water, for example on tank and pit application.
- It should always be connected on a point sensor diversion box FG-DOP before connecting to a locating unit FG-NET-LL, FG-BBOX-LL, FG-ALS8-OD or FG-ALS4-OD having OD BUS 8771 output. The diversion box is not necessary when connecting to a FG-A-OD or FG-STAD.
- The point sensor is compatible with FG-NET-LL, FG-BBOX-LL, FG-ALS8-OD or FG-ALS4-OD Locating Unit (with OD BUS 8771 output). It is also compatible with FG-NET and FG-BBOX digital units (with BUS 8723 output) but need to install an extra interfacing box FG-DOD between (more details see 1.4.7 mixed layout with FG-DOD and FG-DOP on page 18)
- Up to 40 x FG-ODP point sensors per FG-NET-LL or FG-BBOX-LL digital unit circuit.
- Up to 8 x FG-ODP point sensors per FG-ALS8-OD locating unit.
- Up to 4 x FG-ODP point sensors per FG-ALS4-OD locating unit.
- 1 x FG-ODP point sensor per FG-A-OD non-locating unit.
- 1 x FG-ODP point sensor per FG-STAD 'stand-alone' unit.





Figure 1.3.2.1: Layout of point sensor FG-ODP on 4 circuits of FG-ALS4-OD unit using FG-DOP



Figure 1.3.2.3: Layout of point sensor FG-ODP with FG-A-OD or FG-STAD alarm unit using FG-DOP box

Layout Explanation (Figure 1.3.2.1, 1.3.2.2):

- Up to **4** x FG-ODP can be connected to one FG-ALS4-OD locating unit.
- 2 possibilities to connect up to 4 FG-DOP + FG-ODP on FG-ALS4-OD unit: - either 4 point sensors on 4 diffe
 - rent zones (as figure 1.3.2.1); - or on the same zone (as figure 1.3.2.2).

In order to fit the complex installation, TTK offers different kinds of boxes: such as FG-DTC, FG-DTCS, FG-DCTL and FG-DOD. They have their own characteristics but all of them facilitate the extension of the system in different situation. Layouts in session 1.4 explain different situation.

1.4.1 Diversion Box: FG-DTC

• The digital diversion box FG-DTC makes it possible to split a detection circuit into two parts, so as to allow the system to cover more horizontal space (figure 1.4.1).



1.4.2 Addressable Box: FG-DTCS

The addressable sector box FG-DTCS allows connecting digital unit FG-NET with analog sense cables and makes these cables addressable, in the meantime it has a unique advantage to cover vertical space (as illustrated in figure 1.4.2).



DTC cabling diagram

1.4.3 Mixed Layout With FG-DTC & FG-DTCS Boxes

• In real installation, FG-NET system layout could be complex. A mixed installation of FG-DTC and FG-DTCS boxes could ease installation, it allows extension of the system.



Design Tips:

- Use jumper cable for wall or corridor passage between two sense cables. Maximum jumper cable length for each FG-NET output is 150 metre.
- FG-EC cables can be daisy-chained, this is used for horizontal extension (on wide areas on the same floor).
- FG-ECS cables (without connector) has a termination at end tip of the cable, it is recommanded to use for vertical extension (on different floors).

Figure 1.4.3 : Layout with FG-DTC et FG-DTCS boxes

Layout Explanation (Figure 1.4.3) :

- The system uses one FG-DTC box and three FG-DTCS boxes.
- Both ROOM A and COMPUTER ROOM are protected by four FG-EC sense cables. These cables are connected to the first circuit of the panel via a FG-DTC box.
- ROOM B is protected by three sector sense cables FG-ECS via 3 FG-DTCS boxes.
- In this installation, the panel will trigger 3 alarms:
 - leak alarm in ROOM A with +/-1m leak precision;
 - leak alarm in ROOM B indicating the alarming cable;
 - cablebreak alarm in COMPUTER ROOM +/-1m leak precision (all upstream cables in COMPUTER ROOM still functioning).

1.4.4 'Cut-To-Length' Addressable Box: FG-DCTL / FG-DCTL-R

- The FG-DCTL addressable box allows the connection of one analog sense cable (1 to 45m, "Cut-To-Length") to the main BUS wire from the digital panel.
- FG-DCTL will create an address on the panel for that sense cable.
- The LED on the front face of the box indicates the box's status in real time.
- 2 references are available: FG-DCTL and FG-DCTL-R. The only difference: FG-DCTL-R is equipped with a relay (230Vac-1A), activated in case of leak; not for FG-DCTL.
- Maximum 30 FG-DCTL Box per circuit.





Layout Explanation (Figure 1.4.4):

- FG-DCTL is compatible with FG-NET, FG-BBOX and FG-SYS digital units.
- FG-DCTL is compatible with sense cables as FG-ECS and FG-ACS random (length from 1 to 45m).

Figure 1.4.4 : Layout with FG-DCTL interface box

1.4.5 Interface Box: FG-DOD

- FG-DOD is an OD BUS interface box.
- It is used for FG-DD sense cables installed in combination with a water / acids installation on FG-NET / FG-BBOX digital units.
- It will split a standard BUS into two outputs, the first one being ATEX approved and dedicated to FG-OD sense cables, and the second one being dedicated to water / acids sense cables or to another box (see figure 1.4.5.1).



Figure 1.4.5 : Interface box FG-DOD cabling diagram



Figure 1.4.5.1: Connection of interface box FG-DOD



FG-DOD works as an interface between FG-NET digital unit (with TTK BUS 8723 output) and FG-OD sense cables (with OD BUS 8771 output).



Figure 1.4.5.2: Layout of digital unit FG-NET and sense cable FG-OD using interface boxes FG-DOD

1.4.6 Point Sensor Diversion Box: FG-DOP

- FG-DOP is a point sensor diversion box. It is a connection box for integration of the point sensor FG-ODP on an OD BUS 8771. For example, in figure 1.4.6.1 below, the FG-DOP boxes allow the series connection of the point sensors FG-ODP.
- The box is mandatory when connecting on FG-NET-LL, FG-BBOX-LL or FG-ALS4 / 8-OD.
- The box is not required when connecting on FG-A-OD or FG-STAD.
- More layout examples with FG-ALS4-OD see 1.3.2 on page 14.



Figure 1.4.6.1: Layout of point sensor FG-ODP on digital locating unit using FG-DOP

1.4.7 Mixed Layout With FG-DOD & FG-DOP Boxes

A mixed use of boxes FG-DOD and FG-DOP allows the connection of digital units with TTK BUS 8723 (FG-NET, FG-BBOX) outputs to point sensor FG-ODP.



Figure 1.4.7 : Layout of mixed use of FG-DOD and FG-DOP boxes on FG-NET and FG-BBOX units

Layout Explanation (Figure 1.4.7):

- Up to 40 x FG-ODP can be connected to one circuit of FG-NET / FG-BBOX digital unit.
- Up to **10** x diversion box FG-DOP + point sensor FG-ODP can be connected on 1 interface box FG-DOD

FG-SYS / FG-NET Digital Unit has 3 outputs. They can be used for both horizontal and vertical installation for a larger extension. The layout presented below (figure 1.5) is a horizontal layout.



Layout Explanation (Figure 1.5) :

- The system uses all the three outputs of a FG-SYS / FG-NET unit.
- Each output starts from FG-SYS / FG-NET with jumper cable for wall passage till the zone of protection.
- Output 1 goes to room A;
- Output 2 goes to room B;
- Output 3 goes to room C.
- Each output is independent. Room A, B and C are totally independent.

Installation Tips (Figure 1.5) :

- Hold-down clips with adhesive are recommended every 1.5 metres or where required.
- An end termination is indispensable for the last sensing cable of one circuit.

1.6 Vertical Layout On Three Outputs

For a vertical installation in building environment, FG-SYS / FG-NET three outputs are designed for providing extensions to several floors.



Layout Explanation (Figure 1.6) :

- A single digital panel is enough to manage sense cables installed on these three levels.
- Each output starts from FG-SYS / FG-NET with jumper cable for wall passage till the zone of protection.
- On level C, FG-DOD is used for the connection with FG-OD sense cable.
- Each output is independent. Thus floor A, B and C are totally independently under control, to ensure a best security.

Figure 1.6 Vertical layout

In order to fit different installation situation and client's requirements, TTK suggests three typical layouts to protect an area.

Extensive Density Protection



Typical 'very important place' extensive density protection, allowing perimetre and total floor coverage of the room.

Typical application:

Mission critical facilities, data center, hospital, emergency call center, airport control centre, expensive equipments/machines, UPS room, etc.

Perimetre Protection



Typical and the most commun design for prevent external liquid leak come inside the protected zone.

Sensing cable typically installed about 1 metre from the walls.

Typical application:

Offices, archives room, kitchen, toilets, technical room, tank room, lift pit, etc.

Perimetre ACU Protection



Typical design for air-conditionners and leak possible objects, prevent leaks extend without acknowledge.

Sensing cable typically installed about 75cm in front of and near the air-outlet of machines. $% \label{eq:sensitivity}$

Typical application:

ACU room, comms room, vending areas, etc.

Figures 1.7 Three typical layouts

The FG-RELAYS is a digital external relays box. It works as a satellite device of the FG-NET digital unit. It adds a set of 24 configurable external relays to the FG-NET. It allows FG-NET to drive external devices such as solenoid valves, BMS signals, beacons and others, to react in case of leak or system alarms.



Layout Explanation (Figure 1.8) :

- FG-RELAYS N°1, N°2,... N°16 are connected to FG-NET via Ethernet. They are presented as FG-RELAYS #1, FG-RELAYS #2 and so on displayed on the FG-NET Digital Unit.
- FG-RELAYS box status can be viewed on the FG-NET digital unit. In case of box disconnected, FG-NET displays an alarm and the general relay is activated.
- The FG-RELAYS is accessible via a web interface for configuration.
- Up to **16 FG-RELAYS** boxes can be managed by one FG-NET allowing for a maximum of 384 (24x16) additional relays.

2.1 Data Center, Air-Conditioner Room Applications





- This installation is to prevent leaks from the technical equipment.
- For more information about the application examples of FG-OD, refer to hydrocarbon system Design Guides.
- Suitable for dangerous zones of explosive atmosphere – Zener Barrier: Ex ia IIB T4 Ga (ATEX "Zone 0").

2.3 Indoor Water Pipe Application



For pipe with insulation (without drip tray), figure 2.3.1 et figure 2.3.2 present two kinds of water sensing cable installation.





Layout Explanation (Figure 2.3.1 & Figure 2.3.2) :

- The sense cable FG-ECB is installed outside the insulation, on the outside diameter of the mechanical protection sleeve. (Figure 2.3.1);
- The sense cable is installed inside the insulation, on the outside diameter of and under the chilled water pipe (In this case, take into account of condensation phenomena) (Figure 2.3.2).
- Both installations assure an immediate detection for any leak from the pipe, the typical application when the pipes are not
 equipped with the drip tray.

2.4 Application for Several Levels in One Building

FG-SYS / FG-NET locating systems are flexible, from a small area to several big areas, they fit the situation. Both systems have unique advantages in multiple level buildings.



Figure 2.4

Layout explanations (Figure 2.4) :

- The digital unit uses 3 outputs to go to different levels, thus to cover all places that need protection in the whole building.
- Each output has capacity till 600m cables, thus in total 1800m cables can be connected to only 1 digital unit. FG-NET can connect with satellite devices FG-BBOX (up to 1200m of sense cables per device, ref to chapiter 1.7)
- Three possibilities to exploit the information on the digital unit:
- RJ45 port for connecting network-Protocol TCP / IP;
- RS232 or RS422/485series links JBUS / ModBUS protocol;
- 9 relays: 8 fully configurable relays and one specific relay for power failure.
- The alarm panel is installed in ground floor security office for supervising the whole building.